

- [+ Home Theater](#)
- [+ Home Stereo](#)
- [+ Multimedia](#)
- [+ Car Audio](#)
- [+ Custom Install](#)
- [+ Pro Audio](#)
- [+ Drivers](#)

Home > Products > Drivers > Coaxial Ribbon Drivers > S1

S1

S1 2-Way Ribbon Coaxial Mid-Tweeter



Overview

2-Way Ribbon Coaxial Mid-Tweeter

Specifications

Midrange

General Data

Nominal Power Handling (Pnom)(W)	15
Max Power Handling (Pmax)(W)	30
Sensitivity (2.83v/1m)(dB)	88
Weight (M)(Kg)	0.93

Electrical Data

Nominal Impedance (Z)(Ω)	6
DC (Re)(Ω)	5.1

Voice Coil and Magnet Parameters

VC Diameter (mm)	65.5
VC Length (H)(mm)	4.2
VC Former	CCAW
VC Frame	AL
Magnet System	Shielded
Magnet Former	Neodymium

Tweeter

General Data

Nominal Power Handling (Pnom)(W)	6
Max Power Handling (Pmax)(W)	15
Sensitivity (2.83v/1m)(dB)	88

Electrical Data

Nominal Impedance (Z)(Ω)	4
DC (Re)(Ω)	4

Pictures of S1

